


Component Specifications

AXT901, AXT902 Charging Modules

Overview

The AXT901 and AXT902 Charging Modules charge 2 transmitter batteries in the Axient Rackmount Charging Station. Configurable bays in the Rackmount Charging Station allow for mixing and matching of up to 4 charging modules, for a total of 8 handheld or bodypack batteries.

- AXT901 charges 2 AXT910 bodypack transmitter batteries.
- AXT902 charges 2 AXT920 handheld transmitter batteries.
- Fits into Axient Rackmount Charging Stations.
- Rapid charging brings batteries to 50% capacity within 1 hour.
- Completely charges batteries within 3 hours.




AXT901
Bodypack Charging Module

Product Specifications (subject to change)

Charge Current	AXT910: 975 mA AXT920/920SL: 1225 mA
Dimensions	50%=1 hour; 100%=3 hours
Weight	AXT901: 44 g (1.6 oz.) AXT902: 39 g (1.4 oz.)
Housing	Molded ABS, Cast Aluminum

Included Components

30B13476	Mounting Screws for Charger Modules (8)
----------	---



AXT902
Handheld Charging Module

AXT903, AXT904 Portable Charging Stations

Overview

The AXT903 and AXT904 Portable Charging Module charge 2 transmitter batteries in a convenient and compact desktop unit.

- AXT903 charges two AXT910 bodypack transmitter batteries.
- AXT904 charges two AXT920 handheld transmitter batteries.
- Rapid charging brings batteries to 50% capacity within 1 hour.
- Completely charges batteries within three hours.
- Module can be re-used in AXT900 Rack Mount Charging Station.
- Power supply included.

Product Specifications (subject to change)


Battery Type	Up to 2 rechargeable Li-Ion batteries (AXT910/AXT920/920SL)
Charge Time	50%=1 hour; 100%=3 hours
Operating Temperature Range	-18°C (0°F) to +40°C (104°F)
Battery Charging Temperature Range	0°C (32°F) to 60°C (140°F)
Storage Temperature Range	-29°C (-20°F) to 74°C (165°F), without batteries
Dimensions	45 mm x 86 mm x 114 mm (1.8 in. x 3.4 in. x 4.5 in.), H x W x D
Weight	350 g (12.3 oz.), without batteries or PS50 External Power Supply
Housing	Cast and extruded aluminum
Power Requirements	5.5 V DC, 2.72 A

Included Components


AXT901 for bodypack battery or AXT902 for handheld battery	2-bay Charging Module
PS50	Power Supply
30B13476	Mounting Screws for Charger Modules (8)

Optional Accessories

AXT901	2-bay charging module for bodypack battery
AXT902	2-bay charging module for handheld battery



AXT903
Portable Bodypack Charging Station



AXT904
Portable Handheld Charging Station

SHURE[®]

LEGENDARY
PERFORMANCE™

www.axient.net

www.shure.com

©2011 Shure Incorporated

©2015 Shure Incorporated