



A **SHURE**® Company

## JB 6104 Junction Box

- DCS-LAN splitter
- Four tap-out connections
- Supports one conference/discussion unit or one interpreter set at each tap-out
- Alternatively, supports four channel selectors at each tap-out
- Increased system security and flexibility



### Description

The JB 6104 serves as a splitter of the DCS-LAN with four tap-out connections. The unit splits the DCS-LAN into four, single cable connections. Each connection remains unaffected by the other connections. Connecting/disconnecting units or having malfunctioning units on the tap-outs does not affect the remaining system. This provides extra security and flexibility to the overall system.

The JB 6104 supports one conference/discussion unit or one interpreter unit per tap-out. Optionally, four channel selectors can be connected in loop-through per tap-out. The maximum cable length on each tap-out is 10m.

The JB 6104 can be used with any conference unit, interpreter set or channel selector in the DCS 6000 Digital Conference System and can also be used with the DDS 5900 Digital Discussion System.

#### Important:

JB 6104 article no. 15 09 05799 supports only DCS 6000 and is replaced with art. no 15 09 05797.

JB 6104 article no. 15 09 05797 supports both DCS 6000 and DDS 5900 systems.

### Features

The JB 6104 has the following standard features:

- Fully digital audio transmission
- CAT 5e (or higher) F/UTP or U/FTP cabling
- Maximum of four conference units/interpreter sets per JB 6104; one per tap-out
- Maximum of four channel selectors per tap-out
- Maximum cable length of 10m
- Increased system security and flexibility

## Specifications

### Interconnections

<b>DCS-LAN</b>	Two RJ45 female sockets with auto-termination
<b>Tap-out</b>	Four RJ45 female sockets

### Mechanical

<b>Dimensions (H x W x D)</b>	24 x 115 x 70mm
<b>Weight</b>	300 g
<b>Color</b>	Black
<b>Temperature range</b>	5° to 40° C

### Certifications

The DCS 6000 system conforms to standard IEC 60914.

## How To Order

### Junction Box

<b>JB 6104</b>	15 09 05797
----------------	-------------

## DRAWING



# SHURE®

LEGENDARY  
PERFORMANCE™

#### Shure Incorporated

5800 West Touhy Avenue  
Niles, IL 60714-4608  
USA  
Tel. +1 847 600 2000  
Fax +1 847 600 1212 (USA)  
Fax +1 847 600 6446  
info@shure.com

#### Danish Interpretation Systems A/S

Vestre Teglgade 12  
DK-2450 Copenhagen SV  
Denmark  
Tel. +45 33 85 40 40  
Fax +45 33 85 40 41  
salessupport@dis.cc

#### DIS Middle East

LOB 15; Office 221  
Jebel-Ali Free Zone  
P.O. Box 17343  
UAE  
Tel. +971 4 88 71 915  
Fax +971 4 88 71 897  
dubai@dis.cc

#### DIS Asia Pacific

1497 Soi Latphrao 94  
(Town in town 3/2)  
Latphrao Rd., Plubpla  
Wongtonglang  
Bangkok 10310  
Thailand  
Tel. +662 559 3420  
Fax +662 559 3424  
bangkok@dis.cc